MECHANICAL LOCKS

DOOR MOUNTED FOR SMALL SWINGING DOORS

Medium and maximum security.

1010AM DEADLOCK

1010AM-1: KEYED ONE SIDE 1010AM-2: KEYED BOTH SIDE

APPLICATION:

For small swinging doors on access panels, plumbing chases, control cabinets, etc.

FUNCTION:

Mogul key activated locking and unlocking.





DOOR MOUNTED FOR SMALL SWINGING DOORS

Medium and maximum security.

STANDARD FEATURES:

- · Mechanical deadlock
- 6 pin tumblers
- · Mounting fasteners

OPTIONAL FEATURES:


EXTENDED BOLT - Used for stop side mounting. Specify "1-1/4"."

HOLLOW METAL MOUNTING -Used for hollow metal door application. Specify "HM." (See page G17)

MASTER KEYING AVAILABLE.

BOLT KEEPER OPTIONS -(Must be specified separately): 4C - Bolt keeper with dustbox 4CL - Bolt keeper with switch

NOTE: All bolt keepers are supplied with security fasteners.




HOW TO ORDER:

Specify: 1. Quantity


- 2. Swing chart number (handing)
- 3. Bolt projection
- 4. Application (HM or surface)
- 5. Key code instruction
- 6. Bolt keeper requirements


1010AM DEADLOCK





HM Mounting Shown

Swing Chart: Specify circled swing number when ordering









* Indicates lock mounting/access plate side.

TECHNICAL DATA:

- STANDARD FINISH: Galvanized
- COVER: Steel
- CASE: Steel
- LOCKBOLT: Stainless Steel
- MOGUL CYLINDER: US26D
- MOGUL KEYS: Nickel Silver
- PIN TUMBLERS AND ENGAGING BALLS: Combination nickel silver and stainless steel, 6 tumblers per lock.
- LOCK CASE SIZE:
 4.4" L x 3.15" H x 1.35" TK
- · LOCK WEIGHT: 5.5 lbs.
- LOCKBOLT SIZE: 1-1/2" H x 3/4" TK
- LOCKBOLT THROW: 5/8"

