DOOR POSITION SWITCHES FOR SWINGING DOORS

200MRS MAGNETIC SWITCH APPLICATION:

The 200MRS is used where a built-in door indicator switch is desired. This tamper-proof unit is mortised into the door frame. An actuating magnet is recessed into the door edge. Provided with security fasteners.

TECHNICAL DATA:

• SIZE: 4-7/8" L x 1-1/4" W

• WEIGHT: 1 lb.

• ELECTRICAL: 24 volts (AC or DC)

200MRS TB MAGNETIC SWITCH

Triple Bias Switch

220A DOOR POSITION SWITCH APPLICATION:

The 220A switch actuates a remote lamp indicator or an audible signaling device the moment a swinging door is moved from the fully-closed position. Enclosed in a 10 gauge galvanized steel housing, the 220A is designed for installation on the door frame above the top hinge. A pivoting operator that actuates the switch is attached to the door face with special security screws. The 220A is designed for use on doors with 4-1/2" or 5" hinges. Specify hinge size and type (220A-5, 220A-4, etc.). Provided with security fasteners.

TECHNICAL DATA:

• SIZE: 6-5/16" x 2-1/2" x 1-7/8"

· WEIGHT: 3 lbs.

 ELECTRICAL: Switch rating SPDT 15 amps at 125 VAC or .5 amps at 125 VDC

200MRS MAGNETIC SWITCH



220A DOOR POSITION SWITCH







4634 S. Presa Street
San Antonio TX 78223-1000
210-533-1231 Phone • 210-533-2211 Fax

PRODUCT BULLETIN: 13-004

SUBJECT: Product Discontinuation - SS 200MRS and FA ASSW 105A

DATE: March 22, 2013

To: All Customers

The following products are discontinued:

010-1980-400 Folger Adam Magnetic Switch Assembly ASSW 105A with

fasteners. A very limited supply is available for purchase.

010-0734-300 Folger Adam Magnetic Switch Assembly ASSW 105A without

fasteners

76701666/ 76701667 Southern Steel 200MRS Magnet Module (sold as a set)

These products are replaced by:

76701665 Southern Folger 200MRS TB (Triple Bias) Magnetic Door Position

Switch Assembly P/N 76701665

SOUTHERN FOLGER DETENTION EQUIPMENT COMPANY
Kathee Forrest
Product Manager
210-531-2701
kforrest@southernfolger.com



