

## **Lock Mountings**







# Folger Adam





## **Mechanical Locks**

### **Lock Mountings**







#### **Models Available**

- Model G For weldment to flat horizontal bars of a grille door. The lock is installed to the inside of the back plate, and covered by a front plate secured by break-off-head security screws. Specify lock type, handing and thickness of grille door flat bar. Specify with Series 30, 60, 70 or 80 Locks
- Model P For rim mounting a lock to the surface of a plate door. The lock installs to the inside of the mounting, and is then attached to the door. Specify handing. Specify with Series 10, 30, 60, 70 or 80 Locks.

#### **Description**

Detention locks should be enclosed in steel coverings to prevent tampering and abuse. They are removable for service.

#### **Standard Features**

- Rugged construction 7 gauge steel.
- Keying flexibility May be furnished for locks keyed one or two sides.
- Bolt projection Flush after installation.
- Supplied With one No. 1
- Escutcheon and all necessary mounting screws.
- Finish Zinc plated.

#### **Optional Features**

Cylinder shields can be ordered with mountings.

#### **Models Available**

 Model HM – A specially designed plate to which a lock is installed. The plate then covers the lock pocket in a hollow metal door. This mounting is not removable when the door is locked. In stopside applications, a longer bolt projection is required, and must be specified. Specify lock type, handing and hollow metal door thickness. A 1/8" spacer is used between lock and mounting for 2" thick doors.

Specify with Series 10, 17, 30, 60, 70 or 80 Locks.

#### **Dimensional Data**

LOCK MOUNTING	MODEL G			MODEL HM			MODEL P		
	HEIGHT	WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH
With 10 Series lock	N/A	N/A	N/A	5"	7"	3/16"	7-1/4"	5-1/4"	1-7/16"
With 30 Series lock	11-1/2'	10-3/8"	2"	12"	6-1/2"	3/16"	13-1/2"	6-11/16"	1-3/4"
With 60 Series lock	11-1/2'	10-3/8"	2"	7"	10"	3/16"	8-1/2"	9-3/8"	1-3/4"
With 70 Series lock	11-1/2'	10-3/8"	2"	7"	10-3/8"	3/16"	9-3/4"	9-7/8"	1-3/4"
With 80 Series lock	11-1/2'	10-3/8"	2"	7"	10"	3/16"	8-1/2"	9-3/8"	1-3/4"
With 17-M Latch	K/A	N/A	N/A	5"	5-1/2"	3/16"	N/A	N/A	N/A



