



# LOCK MOUNTINGS

## Description

Detention locks should be enclosed in steel coverings to prevent tampering and abuse. They are removable for service.

## Standard Features

- **Rugged construction** – 7 gauge steel.
- **Keying flexibility** – May be furnished for locks keyed one or two sides.
- **Bolt projection** – Flush after installation.
- **Supplied** – With one No. 1 Escutcheon and all necessary mounting screws.
- **Finish** – Zinc plated.

## Optional

Cylinder shields can be ordered with mountings.

## Models Available

- **Model G** – For weldment to flat horizontal bars of a grille door. The lock is installed to the inside of the back plate, and covered by a front plate secured by break-off-head security screws. Specify lock type, handing and thickness of grille door flat bar.

Specify with Series 30, 60, 70 or 80 Locks.



G Lock Mount  
Left hand shown.



P Lock Mount  
Right hand shown.



HM Lock Mount  
Left hand shown.

- **Model HM** – A specially designed plate to which a lock is installed. The plate then covers the lock pocket in a hollow metal door. This mounting is not removable when the door is locked. In stop-side applications, a longer bolt projection is required, and must be specified. Specify lock type, handing and hollow metal door thickness. A 1/8" spacer is used between lock and mounting for 2" thick doors.

Specify with Series 10, 17, 30, 60, 70 or 80 Locks.

- **Model P** – For rim mounting a lock to the surface of a plate door. The lock installs to the inside of the mounting, and is then attached to the door. Specify handing.

Specify with Series 10, 30, 60, 70 or 80 Locks.

For more information, please call 210.533.1231.





# LOCK MOUNTINGS

## How To Order

When ordering mountings, specify hinge or stop side location of mounting plate. Cylinder shields can be ordered with mountings.

## Dimensional Data

LOCK MOUNTING	MODEL G			MODEL HM			MODEL P		
	HEIGHT	WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH
With 10 Series lock	N/A	N/A	N/A	5"	7"	3/16"	7-1/4"	5-1/4"	1-7/16"
With 30 Series lock	11-1/2"	10-3/8"	2"	12"	6-1/2"	3/16"	13-1/2"	6-11/16"	1-3/4"
With 60 Series lock	11-1/2"	10-3/8"	2"	7"	10"	3/16"	8-1/2"	9-3/8"	1-3/4"
With 70 Series lock	11-1/2"	10-3/8"	2"	7"	10-3/8"	3/16"	9-3/4"	9-7/8"	1-3/4"
With 80 Series lock	11-1/2"	10-3/8"	2"	7"	10"	3/16"	8-1/2"	9-3/8"	1-3/4"
With 17-M Latch	N/A	N/A	N/A	5"	5-1/2"	3/16"	N/A	N/A	N/A

